For Residential and Commercial Applications

Job Name	Engineer / Architect	
Job Location	Wholesaler	
Submittal Date	Contractor	

126 Series Hose Barb x Female Iron Pipe Adaptor

Use: For use plastic or rubber tubing. Installation requires a hose clamp.

Design Features:

- Manufactured with dryseal pipe threads
- Available in a broad range of sizes

Operating Specifications:

Temperature: -40° to 160° F **Working Pressure:** 150 PSI

l]
		\
l		7
l]
		\
l		7
لبسي	'	L

FITTING MATERIAL SPECIFICATIONS Body Brass

Part Listing:

	y.	
	126-2-2	1/8" hose barb x 1/8" FIP
	126-3-2	3/16" hose barb x 1/8" FIP
	126-3-2 B	3/16" hose barb x 1/8" FIP, bulk
	126-4-2	1/4" hose barb x 1/8" FIP
	126-4-2 B	1/4" hose barb x 1/8" FIP, bulk
	126-4-4	1/4" hose barb x 1/4" FIP
	126-4-4 B	1/4" hose barb x 1/4" FIP, bulk
	126-5-2	5/16" hose barb x 1/8" FIP
	126-5-2 B	5/16" hose barb x 1/8" FIP, bulk
	126-5-4	5/16" hose barb x 1/4" FIP
	126-6-2	3/8" hose barb x 1/8" FIP
	126-6-2 B	3/8" hose barb x 1/8" FIP, bulk
	126-6-4	3/8" hose barb x 1/4" FIP
	126-6-4 B	3/8" hose barb x 1/4" FIP, bulk
	126-6-6	3/8" hose barb x 3/8" FIP
	126-6-6 B	3/8" hose barb x 3/8" FIP, bulk
	126-6-8	3/8" hose barb x 1/2" FIP
	126-6-8 B	3/8" hose barb x 1/2" FIP, bulk
	126-8-4	1/2" hose barb x 1/4" FIP
	126-8-4 B	1/2" hose barb x 1/4" FIP, bulk
П	126-8-6	1/2" hose barb x 3/8" FIP





126 Series Hose Barb x Female Iron Pipe Adaptor

Part Listing (con't):

126-8-6 B	1/2" hose barb x 3/8" FIP, bulk
126-8-8	1/2" hose barb x 1/2" FIP

126-12-12 3/4" hose barb x 3/4" FIP





PART DIMENSIONS (Inches)						
Model	DIA. A	DIM. B	DIM. C	DIA. D	HEX. E	
126-2-2	.187	.46	.96	.090	1/2	
126-3-2	.227	.69	1.19	.125	1/2	
126-4-2	.290	.97	1.47	.187	1/2	
126-4-4	.290	.97	1.58	.187	11/16	
126-5-2	.375	.90	1.42	.215	1/2	
126-5-4	.353	.97	1.58	.250	11/16	
126-6-2	.415	.97	1.47	.281	1/2	
126-6-4	.415	.97	1.58	.281	11/16	
126-6-6	.415	.97	1.63	.281	13/16	
126-6-8	.415	.97	1.73	.281	1	
126-8-4	.530	.97	1.66	.375	5/8	
126-8-6	.530	.97	1.63	.375	13/16	
126-8-8	.530	.97	1.73	.375	1	
126-12-12	.790	1.17	2.19	.625	1-3/16	