



PRODUCT DESCRIPTION

By uniting a romantic shape with a stunning circle of brilliant light, we created an Eternity™ that encapsulates a clear vision of renewal and balance, boldly illuminating your space with timeless elegance.

SPECIFICATION STATEMENT

Solution shall consist of a lighted mirror with forward-facing task lighting as well as wall-glow ambient lighting around the mirror. Mirror shall have corrosion-resistant glass and have uniform light output in frosted areas, using dimmable, replaceable LEDs with greater than or equal to 90 CRI (color rendering index). Product will be made in USA and have a 7-year limited warranty.

THE ELECTRIC MIRROR ADVANTAGE

- ☑ Global mirror technology leader for over 20 years
- ☑ More installations than all competitors combined
- ☑ Realistic warranty you can believe in and trust
- ☑ Lowest total cost of ownership
- ☑ U.S. based customer service support
- ☑ 125,000 square foot American manufacturing facility

FEATURES AND BENEFITS

- Copper-free, corrosion-resistant DuraMirror™ glass
- Forward-facing task lighting
- Wall-glow ambient lighting with diffuser for a finished side view
- Environmentally sustainable
- Energy efficient
- Fast lead times
- Easy installation
- Title 24 compliance available
- 7-year limited warranty
- Covered by one or more patents
- Proudly made in the USA

AVAILABLE OPTIONS

- Ava™ SmartLook™ Technology^{1, 2}
- Keen™ SmartDim™ Technology¹
- Vive™ SmartSound™ Technology^{1, 2}
- Seamless™ SmartTime™ Technology^{1, 2}
- Defogger¹
- Forward-phase dimming
- Diamond Clear™ DuraMirror™ glass²
- 2,700K CCT²

LIGHTING SPECIFICATIONS

- Natural-looking LED light color
- Replaceable LEDs
- CRI: 90+
- CCT: 3,000 Kelvin
- 604 lumens per foot
- Calculated L₇₀ 124,000-hour LED lifespan
- Maximum 100 lumens per watt efficacy

SAFETY SPECIFICATIONS

- Entire assembly meets UL/cUL standards
- International certifications
- Safety-backed mirror

¹ See technology specification sheets for more information.

² Minimum order quantity required.

INSTALLATION SPECIFICATIONS

- 120V-240V hardwire electrical connection; provide 12" whip; junction box not required
- Chassis should be mounted to wall studs; mounting holes are provided
- Fixture should be controlled by an on/off switch
- Installation wiring may be different on mirrors equipped with additional options

MODELS

| Base Model* | Dimensions | Power Requirements |
|-------------------------|---|--------------------|
| ETE2-21.00x30.00-L7-30K | 21"W x 30"H x 1.75"D (Oval) (533mm x 762mm x 44mm) | 120/240 VAC, 34W |
| ETE2-30.00-L7-30K | 30" diameter x 1.75"D (762mm x 44mm) | 120/240 VAC, 40W |
| ETE2-36.00-L7-30K | 36" diameter x 1.75"D (914mm x 44mm) | 120/240 VAC, 51W |

*Base model number shown only. To specify additional options, contact Electric Mirror at sales@electricmirror.com.

DIMENSIONAL DRAWING (Not to scale. Frost and border widths may vary depending on mirror size.)

