

GEBERIT SIGMA21 ACTUATORS

For Sigma Concealed Tanks, 2x6 and 2x4 Installations

SPECIFICATIONS

Actuators for concealed tank and carrier system. Actuator flush plates and push buttons shall be glass or slate with zinc diecast base unit. All components shall be compliant with applicable codes and product standards.

FEATURES

- Designed to maintain appearance push after push
- Moving parts are accessible behind actuator flush plate
- Made of glass or slate with zinc die-cast base unit
- Customizable overlay available
- Incorporates water saving possibilities when used with Geberit dual-flush tanks 1.6 GPF (6 LPF) and 0.8 GPF (3 LPF) or 1.28 GPF (4.8 LPF) and 0.8 GPF (3 LPF)
- Includes mounting frame and hardware

WARRANTY

One-year limited warranty


Dual-Flush Actuators, Sigma 2x6 Installation

Ł

Style	Material	Finish	Model No.
Sigma21	Die-Cast	Customer supplied overlay	115.884.00.1
00	Slate	Natural	115.884.JM.1
	Glass	White Glass	115.884.Sl.1
		Black Glass	115.884.SJ.1
		Sand Glass	115.884.TG.1

DIMENSIONS

Sigma21 Dual-Flush



Products marked with comply with the American Disabilities Act (ADA) when installed per the requirements of the latest ADA Accessibility Guidelines (ADAAG) and/or ICC/ANSI A117.1.



Job Name:	
Date:	Quantity:
Model Specifi	ed:
Variations Sp	ecified:
Customer/Wh	olesaler:
Contractor:	
Architect:	



Geberit 2100 S. Clearwater Drive Des Plaines, IL 60018 USA

P 847-803-7777 F 847-803-5454

www.geberit.us