TOTO₈

MW644584CEFG

Carolina[®] II / WASHLET[®]+ S350e One-Piece Toilet - 1.28 GPF

FEATURES

- Concealed supply connection for seamless installation
- High-efficiency Tornado Flush® (1.28GPF/4.8LPF)
- Skirted design
- CeFiONtect[®] glaze prevents debris from sticking to ceramic surfaces for easy cleaning
- Universal Height
- Decorative one-piece design with high-profile tank
- Elongated front bowl
- 12" Rough-in, less supply
- Optional 10"; 14" Uni-fit rough-in
- Chrome trip lever
- Auto open/close lid
- See Spec sheet SW584T20 for Washlet features

MODELS

• CST644CEFGT20 With CeFiONtect glaze

REQUIRED WASHLET+

• SW584T20 WASHLET®+ S350e Fits TOTO WASHLET+ toilet bowl models only

COLORS/FINISHES

 Standard #01 Cotton

OPTIONAL ROUGH-IN

- 10" rough-in TSU01W.10R
 - 14" rough-in TSU01W.14R

PRODUCT SPECIFICATION

The one-piece high-efficiency Tornado Flush toilet shall be 1.28GPF/4.8LPF. Universal Height Toilet with CeFiONtect glaze finish. Toilet shall have high-profile tank, elongated front bowl and chrome trip lever. Toilet shall be **TOTO Model CST644CEFGT20#01**.

See TOTO Specification sheet **SW584T20** for details on required Washlet.





CODES/STANDARDS

- Meets and exceeds ASME A112.19.2/CSA B45.1
- Certifications: IAPMO(cUPC), EPA WaterSense, State of Massachusetts, City of Los Angeles, and others
- Code compliance: UPC, IPC, NSPC, NPC Canada, and others
- Legislative Compliance: California AB715, California Green Building Code, City of Los Angeles Water Efficiency Ordinance
- ADA compliant (when installed with trip lever located on the approach side)



MW644584CEFG

Carolina[®] II / WASHLET[®] + S350e One-Piece Toilet - 1.28 GPF

SPECIFICATIONS

- 1.28 GPF/4.8LPF Water Use
- Flush System .

Tornado Flush®

- Min. Water Pressure 8 psi (flowing)
- Water Surface 6-7/8" x 9-3/4" 2-1/8"
- Trap Diameter
- Rough-in
- Trap Seal 2-1/8"
- Warranty One Year Limited Warranty


12"

- Material
- Vitreous china Shipping Weight CST644CEFGT20 108lbs.
- SW584T20 13.5lbs.
- Shipping Dimensions CST644CEFGT20 29-1/2" L x 18"W x 19-1/4" H¹ x 27-1/8" H² SW584T20 23"X 19-1/4" X 5-1/2"
- See Spec sheet SW584T20 for Washlet details

INSTALLATION NOTES

Back-to-Back Toilet Installations:

TOTO recommends the use of a nationally listed, double sanitary tee-wye only, in vertical waste stacks, in accordance with the stipulations noted in the majority of nationally recognized plumbing codes.



To maintain adequate wall gap between the back of the tank and wall, mount the floor flange at a nominal 12" rough-in distance.

